


Lifetime™ Waterproofing Sealant System

APPLICATION METHODS

SPRAYING: Spraying can be used on vertical or horizontal surfaces.

For Best Results:


- Be sure the sprayer is clean and free from other chemicals
- The nozzle should remain 6-12 in from other chemicals
- Respray each section 2-3 times as penetration allows
- Backroll excess material that has not penetrated.
- On vertical surfaces, spray from top to bottom.
- Clean equipment with mineral spirits or paint thinner immediately after applying Lifetime™



COMPRESSED AIR TANK SPRAYER (with solvent resistant fittings)

The sprayer can be used on vertical or horizontal surfaces, it is important to backroll excess material that has not penetrated. Always


be sure that the sprayer is clean and free from chemical or insecticide residue. Clean equipment with mineral spirits or paint thinner immediately after use of Lifetime™.



AIRLESS SPRAYER

Lifetime™ can be used with an airless sprayer if care is taken to use the equipment properly. To ensure proper application apply Lifetime™ with a 421 Contractor Spray Tip, not to exceed 500 psi. The


nozzle should remain 6-12 inches from the surface and move in straight even strokes. Clean equipment with mineral spirits or paint thinner immediately after use of Lifetime™.



BRUSH, ROLLER, PAINT PAD

Lifetime™ can be applied with a brush, roller or paint pad. Clean equipment with mineral spirits or paint thinner immediately after use of Lifetime™.

- 1 **Brush** may be either natural or foam
- 2 **Roller** can be foam, where dark lines are created by the ends of the roller, backroll them immediately.
- 3 **Paint Pad:** apply in a straight line and overlap with each stroke.



DIPPING

Shingles, shakes or wood siding can be dipped prior to installation. This is an effective way of applying Lifetime™. It assures complete coverage and thorough saturation of the front, back and ends of the

wood. You should wipe off excess material.

COVERAGE PER GALLON

Surface Type	Sq. Ft.	Sq. M.
Stucco	170	15.8
Wood Shingles	110	10.2
Fencing	125	11.6
Decking	140	13
Driveways / Concrete	150	13.9
Stone – smooth	170	15.8
Stone – rough	130	12
Exterior Brick	120	11.2

PLEASE NOTE: These are estimates and may vary considerably due to the porosity of the recipient material.

FOR BEST RESULTS:

- **TEST APPLICATIONS SHOULD ALWAYS BE MADE**
- Make sure the surface to be treated is clean and dry. It is best to apply a small inconspicuous test patch to check for aesthetics and penetration.
- Lifetime™ Waterproofing Sealant can be applied with a brush, roller, broom or airless spray. With an airless spray use low pressure for all surfaces other than shake shingle roofing, where high pressure is recommended to allow application of product underneath the shingle.
- Lifetime™ Waterproofing Sealant can be applied to horizontal or vertical surfaces. It is applied from top to bottom on vertical surfaces. Flood coat the material on vertical surfaces so that a 6 – 8 inch run down is achieved.
- Application of Lifetime™ should cover material completely but avoid puddling on the surface.
- Clean equipment immediately after use with mineral spirits or paint thinner.
- If you partially use a container, reseal it immediately and completely.
- Lifetime™ Waterproofing Sealant must be used as supplied by factory or distributor, without the use of solvents, catalysts or curing agents.

WARNING AND CAUTION

- Read, understand, and follow the Material Safety Data Sheet supplied with the material before use.
- Apply in a well-ventilated area.
- Avoid contact with eyes and skin.
- Avoid breathing mist or vapor.
- Overspray on foliage will damage the plant.

EMERGENCY FIRST AID INSTRUCTIONS:

- Ingestion: Do not induce vomiting. **GET MEDICAL ATTENTION.**
- Eyes: Flush with water.
- Skin: Wash with soap and water.
- Please – Read the instructions and warnings on the container.